




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B60R 22/28	A1	(11) International Publication Number: WO 98/36951 (43) International Publication Date: 27 August 1998 (27.08.98)
(21) International Application Number: PCT/US98/02988 (22) International Filing Date: 17 February 1998 (17.02.98) (30) Priority Data: 801,234 19 February 1997 (19.02.97) US (71) Applicant: BREED AUTOMOTIVE TECHNOLOGY, INC. [US/US]; P.O. Box 33050, Lakeland, FL 33807-3050 (US). (72) Inventors: MILLER, H. John, III; 19398 Hillside, Macomb Township, MI 48044 (US). KELLER, Gerald; 52137 Blue Bell, Shelby Township, MI 48316 (US). (74) Agent: SEITZMAN, Markell; Breed Automotive Technology, Inc., 7000 Nineteen Mile Road, Sterling Heights, MI 48314 (US).		(81) Designated States: BR, JP, KR, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: MULTI-LEVEL LOAD LIMITING TORSION BAR RETRACTOR**(57) Abstract**

An energy absorbing retractor having a frame (22), locking mechanisms (56, 60, 60a, 66, 66a) to initially stop a spool (30) from rotating in a belt protraction direction and bias means (80) to retract the seat belt. A two sided torsion bar (200) for generating at least first and second levels of reaction torque on the spool permits the spool to rotate in a controlled manner in a belt protracting direction. The torsion bar (200) has a middle portion (202) fixedly coupled to the spool and first and second torsion members (206a, 206) extending therefrom. The ends (208) of the torsion members are respectively coupled to a first locking mechanism (56, 60) and a second locking mechanism (56, 60a) to prevent the first and/or the second end from rotating upon such coupling, whereby upon locking of the first and/or second end, and loading of the spool, the first and/or second torsion members are twisted to generate different levels of control force.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MULTI-LEVEL LOAD LIMITING TORSION BAR
RETRACTOR

BACKGROUND AND SUMMARY OF THE INVENTION

5 The present invention generally relates to seat
belt retractors which include a means for absorbing
or dissipating crash energy. More particularly, the
present invention relates to a seat belt retractor
having a multi-level reaction force generating
10 torsion bar therein.

 In a conventional seat belt retractor, a web or
a vehicle (often called inertial) sensor is used to
stop the rotation of a spool to prevent the
protraction of the seat belt webbing during an
15 accident. A second class of seat belt retractors
permits the controlled protraction of the seat belt
by incorporating within the retractor an energy
absorption (or dissipation) mechanism which permits
the spool to rotate after the retractor has been
20 initially locked up. In the past these mechanisms
have included crushable bushings (U.S. Patent
5,547,143), deformable tubes (U.S. Patent 3,881,667)
or torsion bars (U.S. Patent 3,741,494).

 It is an object of the present invention to
25 provide an energy absorbing retractor that has one
or more load limiting levels, a retractor that may
be activated either mechanically or electrically,
and one which utilizes a unique energy absorbing
(dissipating) mechanism.

-2-

Accordingly the invention comprises: an energy absorbing retractor having a frame, locking mechanisms to initially stop a spool from rotating in a belt protraction direction, the spool being
5 rotationally supported relative to the frame, a seat belt wound about the spool, bias means to retract the seat belt, and torsion bar means for generating at least a first level of reaction torque on the spool permitting the spool to rotate in a
10 controlled manner in a belt protracting direction including a torsion bar having a middle portion and a first torsion rod (or torque or torsion tube) extending therefrom, the middle portion fixedly coupled to the spool to prevent relative rotation
15 therebetween, the first torsion rod including a first end coupled to first locking mechanisms to prevent the first end from rotating upon such coupling, whereby upon locking of the first end, and the loading of the spool, the first torsion rod is
20 twisted, permitting the spool to rotate, to generate a first level of control force. A second torsion rod (or torque or torsion tube) is provided which can generate a second level of reaction force. A third level of reaction force is attainable if both
25 torsion rods are activated.

Many other objects and purposes of the invention will be clear from the following detailed description of the drawings.

-3-

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIGURE 1 is a front plan view of the present invention.

5 FIGURE 2 is an isolated isometric view showing an axle assembly.

FIGURE 3 is an isometric view illustrating a lock cup, vehicle sensor and solenoid.

10 FIGURE 4 is a left-side isometric view of a retractor illustrating a locking mechanism and solenoid.

DETAILED DESCRIPTION OF THE DRAWINGS

Reference is made to the drawings which show a
15 cross-sectional view of a seat belt retractor 20 constructed in accordance with the present invention. The retractor includes a U-shaped frame 22 having frame sides 24a and 24b and a rear portion 24c. Part 24c includes a mounting opening 26. Each
20 side 24a and b includes a respective circular opening 28a and 28b. Rotatably supported on the frame 22 is a spool generally shown as 30. The spool includes a center portion 32 and flanges 34a and 34b. A length of seat belt webbing 36 is wound
25 upon the center part of the spool. An inner end of the seat belt is received within a slot 37 formed within the spool in a known manner. The spool 30 further includes a central, stepped through bore 40 having a narrow center section 42 and two opposing
30 wider end sections 44a and 44b. The narrow section

-4-

42 includes internal teeth or splines 46 as are more clearly shown in FIGURE 2.

Situated in the through bore 40 is an axle assembly 198 comprising a torsion bar assembly 200
5 having a center section 202 having splines 204 which mate with splines 46 of the through bore 40 to prevent the center section 202 of the torsion bar assembly from rotating relative to the spool 30. The torsion bar assembly includes a first extending
10 torsion rod 206 which terminates in a splined section 208. The diameter of the splined section 208 is larger than the diameter of the torsion bar 206. Extending from the center section 202, opposite to rod 206, is a second torsion rod 206a
15 which terminates in a splined section 208a. Either torsion rod 206 or 206a can be replaced by a torque or torsion tube 206' shown in phantom line. In the preferred embodiment of the invention the diameter of torsion rod 206 is larger than the diameter of
20 torsion rod 206a. The reason for the dissimilar torsion rods 206 and 206a (or tubes 206') is to permit the generation of different levels of reaction force when one or the other of the torsion rods or tubes is twisted.

25 The axle assembly 198 further includes end portions 210. Each end portion 210 includes a hollow body 212 having splined bore 214. The splined ends 208 and 208a of the torsion bar 200 are received within a respective splined bore 214 of
30 each end assembly 210. Each body 210 includes a

-5-

narrow first portion 216 received within the through bore 40 for providing a bearing surface about which the spool 30 can rotate, a first shoulder 218 which is received within an annular groove 220 of the

5 spool 30 which acts as a thrust bearing to absorb lateral loads and to laterally stabilize the spool 30. Each end assembly 210 further includes a second portion 222 which is received within respective opening 28a and 28b in the retractor frame 22. Each

10 opening operates as a bearing to rotationally support the axle assembly 198. If desired a separate bearing can be inserted in the openings. Positioned adjacent the second portion of each end assembly 210 is a third portion 230 upon which is

15 received a respective lock wheel 56 having lock teeth 58. The lock wheels can be positioned upon the second portion 222 in which case the third portion of each end assembly 210 is received within the frame openings 28a,b such that the lock wheels

20 are positioned in-board of the frame sides 24a,b between the sides and the flanges of the spool. Each end assembly 210 further includes a ratchet wheel 74 or 74a having teeth 76 (and 76a). The ratchet wheels can be formed as an integral part of

25 each end assembly or attached thereto.

As will become apparent from the description below the retractor 20 includes two independently activated energy absorbing mechanisms which in this present invention are formed by the two torsion rods

30 206 and 206a, the end assemblies 210 and associated

-6-

locking mechanisms. These energy absorbing mechanisms will permit the spool 30 to rotate relative to the axle assembly 198 when the seat belt is loaded by the occupant during an accident. The
5 energy absorbing mechanisms will each generate a reaction force controllably impeding the rotation of the spool and the protraction of the seat belt. The energy absorbing mechanisms, as described below, will permit the generation of two different levels
10 of controlled reaction force if activated independently and a third level of reaction force if activated simultaneously.

The lock teeth 58 of each lock wheel 56 are engaged by rotationally mounted lock pawls 60 (and
15 60a) (see FIGURES 1, 3 and 4) pivotally supported on pins 61 on opposing sides of the frame 22. Each lock pawl 60 and 60a includes an extending pin 62 which is received within a cam surface 64 of a respective lock cup 66 or 66a located on opposite
20 sides of the retractor frame. One such lock cup is shown in European Patent Application EP 0 228 729 A1 which is incorporated herein by reference. As is known in the art retractors include a web sensor (to initiate lock-up of the retractor when the webbing
25 is protracted at a determinable level) and a vehicle sensor. Such a web sensor (not shown) is included within the lock cup 66a. Each lock cup 66 or 66a includes a plate 70.

Returning to the figures, in the present case,
30 the torsion bar assembly 200 includes an extending

-7-

stub axle 214 which extends from the splined portion 208 of the torsion bar assembly 200. Lock cup 66 is loosely secured about the stub axle 214.

Extending from the other end of the torsion bar 200
5 is a second stub axle 214a which acts as a spring arbor to receive an end of a return spring 80 which is used to rewind the seat belt 32 upon the spool 30. Lock cup 66 is loosely secured about stub axle 214.

10 As mentioned above each splined portion 208 and 208a of the torsion bar 200 is received within a corresponding splined portion 214 of the end assemblies 210. This construction rotationally fixes each splined portion to its end assembly 210.

15 Additionally, by virtue of this connection, the stub axles 214 and 214a rotate with the respective end assemblies 210 and their ratchet wheels 74 and 74a.

The lock cup 66a (attached to frame side 24b) includes a web sensor, which is not illustrated,
20 (which is not the case for lock cup 66) comprising an inertial mass which is located within the lock cup, which moves to engage internal teeth 78 of the ratchet wheel or lock cup when the seat belt webbing is protracted at a rate greater than a predetermined
25 level, thereby linking the plate 70 of latch cup 66a with the ratchet wheel 74a and axle 72a, causing the lock cup 66a to rotate, thereby moving the lock pawl 60a into engagement with its mating lock teeth 58.

As mentioned above such a construction is generally
30 known in the art.

-8-

Reference is made to FIGURE 3, which shows a vehicle (inertia) sensor generally shown as 82 which is associated only with lock cup 66a. The various parts of the lock cup are slightly separated for ease of illustration. This is true of FIGURE 4 as well. In the illustrated embodiment this vehicle sensor is a standing man sensor having an inertial element 84 which tips relative to a center axis 86 when the vehicle decelerates greater than a predetermined level. The vehicle sensor 82 is situated upon, movable with and is supported on plate 70 of the lock cup 66a. Also pivotably mounted to the plate 70 of the lock cup 66a about pin 90 is a sensor pawl generally shown as 92. The sensor pawl includes a toothed portion 94 which is moved into engagement with the ratchet wheel teeth 76a and an extending arm 96. Also supported on plate 70 of lock cup 66a is an electrically responsive solenoid 100 having a movable plunger 92 with a slot 104 formed therein. As can be seen, the arm 96 is received through the slot 104. The slot 104 is oversized such that during normal operation of the vehicle, motion of the sensor pawl 92, caused by motion of the sensor 82, is not interfered with by the plunger 102. During normal operation of the vehicle involving a relatively high level of vehicle deceleration (which might occur in an accident or as a result of severe brake application), the inertial sensor will tip which in turn causes the sensor pawl 92 to rotate about its pivot 90 moving its toothed

-9-

portion 94 into mating engagement with the teeth 76a on the ratchet wheel 74a. This coupling links the lock cup 62a to the axle, causing the lock cup 66a to rotate and to move the lock pawl 60a into
5 engagement with the lock wheel, preventing protraction of the seat belt webbing from the spool 30.

Lock cup 66 (see FIGURE 4), located on side 24a of the frame, supports a second solenoid 100' having
10 a plunger 102' that is pivotably connected via pin 202 to a sensor pawl 92' (which is substantially identical to sensor pawl 92) that is pivoted about a pin 90 associated with the plate 70 of the lock cup 66. Upon activation of solenoid 100', the sensor
15 pawl 92' is moved upwardly into engagement with the teeth 76, coupling the lock cup 66 to the motion of the axle assembly 110, thereby moving pawl 60 into engagement with its corresponding lock wheel 56. Lock cup 66 does not include a web or inertia sensor
20 but these sensors could be incorporated therein.

The following illustrates the operation of the present invention. During the normal operation of the retractor, the webbing can be protracted as the occupant moves forward and retracted by the rewind
25 spring as the occupant returns to the normal seated position. As mentioned above, the retractor includes a mechanical locking mechanism comprising a web sensor and a mechanical vehicle sensor 82. During the normal operation of the vehicle, there
30 may be non-accident instances where the webbing is

-10-

pulled out at a rate which will activate the web sensor, or the vehicle is decelerated at a level which would activate the mechanical vehicle sensor 82 thereby bringing the associated locking pawl 60a
5 into locking engagement with its lock wheel, thereby halting the protraction of the seat belt webbing.

There will be instances, however, where the vehicle is involved in a crash. Such a crash, as sensed by an appropriate crash sensor (not shown),
10 will typically involve deceleration levels that are greater than that which would be achieved during normal operation of the vehicle.

On sensing a crash of a first level, an electronic control unit, generally shown as 200,
15 associated with a crash sensor will generate a first activation signal which will cause the plunger 102' to move upwardly a sufficient amount, such that the arm 96' of the sensor pawl 92' will be lifted into engagement with the lock teeth, thereby coupling the
20 lock cup 62 to the retractor axle and causing the lock pawl 60 to move into engagement with the lock wheel, thereby momentarily locking the spool and prohibiting the protraction of the seat belt. The action of the solenoid 100' will typically precede
25 similar motion of the mechanical inertia sensor 82 which would also move the pawl 92 into engagement with the ratchet wheel 74a. During the crash, the occupant will typically move forwardly, loading the seat belt. These forces are transmitted directly to
30 the webbing 36 and to the spool 30. As these forces

-11-

or torques increase, the spool 30, through its splined connection to the torsion bar 200 will rotate as torsion rod 206a twists. It should be appreciated that the splined end 208 of the torsion
5 rod 206a will not rotate after its corresponding lock wheel 56 is locked. As the crash forces increase the spool 30 will be rotated in a direction of seat belt protraction and simultaneously be resisted by the reaction forces generated by torsion
10 rod 206a as it continues to twist. In this manner, during a crash of a first level or magnitude, the manner in which seat belt is permitted to protract and the forces input to the occupant via the seat belt are controlled. As can be appreciated, since
15 lock cup 66 has no mechanical inertia sensor or web sensor, its activation is entirely electrical.

If the ECU 200 determines that the crash is at the first level, the ECU will generate a control signal which causes the plunger 102 to be maintained
20 in its lower position, thereby preventing the activation of lock cup 66 by the mechanical sensor 82.

If the ECU 200 determines that the vehicle is involved in a crash of a greater second level, the
25 ECU will generate a control signal to activate solenoid 100 which is carried by lock cup 60a situated relative to frame side 24b. Upon activation of solenoid 100, the sensor pawl 92 is moved upwardly into engagement with the teeth 76a,
30 coupling the lock cup 66a to the motion of the

-12-

corresponding end assembly 210, thereby moving pawl 60a into engagement with its corresponding lock wheel 56 locking the end assembly 210 of the axle assembly (and the splined end 208 of the torsion rod 206a). During this crash, the torsion rod 206 (which is thicker than torsion rod 206a) will be twisted as the spool rotates generating (as with the twisting of rod 206a) a predetermined reaction force proportionally to the physical characteristics of the torsion rod 206 to a) control the forward motion of occupant and b) to control the dynamics of the protraction of the seat belt in the manner similar to that described above. To achieve three levels of reaction torque is desirable to make torsion rod 206 dissimilar from torsion rod 206a so that the retractor may generate a different level of reaction force retarding the motion of the occupant in correspondence to the activation of the locking mechanisms including the lock cups 66 and 66a.

If the ECU 200 determines that the crash is of a significantly high level requiring the generation of a high retarding force on the seat belt, this will be accomplished by simultaneously generating control signals to both solenoids 100 and 100', thereby causing both lock pawls 60a and 60b to respectively lock both sides of the torsion bar assembly 200. As can be appreciated, any rotational motion of the spool will not be resisted by the forces necessary to twist both torsion rods 206 and 206a.

-13-

In summary, it can be seen that the present retractor can generate a multi-level retarding force by activating one or the other of the energy dissipating members of the present invention, or alternatively, can generate a third level of retarding force by activating both energy absorbing members simultaneously. It should also be appreciated that by virtue of the incorporation in the present invention of the solenoid 100 and inertial mass sensor 82, which both act upon and move the sensor pawl 92, that the present invention provides a high degree redundancy in its operation in that if for some reason the ECU 200 could not or does not generate the appropriate activation signals to the solenoids 100 or 100', the inertial sensor 82 will have moved the sensor pawl 92 into locking readiness with the ratchet wheel 74a, which in turn causes lock pawl 60a to move into engagement with its corresponding lock wheel. If the forces that are generated on the seat belt are sufficiently high, the spool 30 will rotate and in doing so be resisted by both energy absorbing mechanisms.

As can be appreciated from the above, the level of control force generated by the energy absorbing mechanisms to oppose the rotation of the spool 30 and permit the controlled protraction of the seat belt will vary with the size of individual torsion rods 206 and 206a. Further, it may be desirable to size the torsion rod associated with the mechanical inertia sensor to generate a level of control force

-14-

associated with a moderate or high level crash as the inertia sensor provides for redundancy and to size the other (electrically activated) energy absorbing mechanism (torsion rod 206) to generate a
5 control force when the vehicle is involved in a lower level accident.

Many changes and modifications in the above described embodiment of the invention can, of course, be carried out without departing from the scope
10 thereof. Accordingly, that scope is intended to be limited only by the scope of the appended claims.

-15-

Claims

1. An energy absorbing retractor (20) having
a spool,
5 a frame (22), a locking mechanism (60, 60a, 56,
66, 66a) to initially stop the spool (30) from
rotating in a belt protraction direction, the spool
rotationally supported relative to the frame,
a seat belt (36) wound about the spool, and
10 bias means (80) to retract the seat belt,
torsion means (200, 206, 206a) for generating
at least a first level of reaction torque on the
spool permitting the spool to rotate in a controlled
manner in a belt retracting direction including a
15 torsion mechanism having a middle portion (202) and
a first torsion member (206a) extending therefrom,
the middle portion fixedly coupled to the spool to
prevent relative rotation therebetween, the first
torsion member including a first end (208) coupled
20 to first locking mechanism (66, 58) to prevent the
first end from rotating upon such coupling, whereby
upon locking of the first end, and the loading of
the spool, the first torsion member (206a) twists to
generate a first level of control force.
25
2. The apparatus as defined in Claim 1 wherein the
torsion mechanism (200) includes a second torsion
member (206a) extending from the middle portion
opposite to the first torsion member (206), the
30 second torsion member including a second end (208)

-16-

coupled to a second locking mechanism (66a, 58) to prevent the second end from rotating upon such coupling, whereby upon locking of the second end, and the loading of the spool, the second torsion member twists to generate a second level of control force.

3. The device as defined in Claim 2 wherein the first and second levels are different.

4. The device as defined in Claim 2 wherein the retractor includes control means (200) for locking the first and second ends of the first and second torsion members relatively simultaneously.

5. The apparatus as defined in Claim 2 wherein one of the first or second locking mechanisms includes a mechanical inertial sensor means for initiating the locking up of an end of the torsion mechanism and wherein the retractor includes lock-out means (100, 200) for preventing the sensor means from locking the torsion mechanism.

6. The apparatus as defined in Claim 2 wherein the torsion members are torsion rods.

7. The apparatus as defined in Claim 2 wherein the torsion members are torsion tubes.

1/4




FIG. - 1

2/4




FIG-2

3/4





FIG. - 3

4/4**FIG. - 4**

INTERNATIONAL SEARCH REPORT

 International application No.
PCT/US98/02988

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B60R 22/28

US CL :242/379.1; 280/805

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. 242/379.1; 280/805, 806; 297/470, 471, 472

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- A	US 5,522,564 A (SCHMIDT et al) 04 June 1996, note middle portion 26 and torsion member 25, see col. 9, lines 21-33.	1 --- 2-7
A	US 5,526,996 A (EBNER et al) 18 June 1996, see whole document.	1-7
A, P	US 5,611,498 A (MILLER III et al) 18 March 1997, see whole document.	1-7
A, P	US 5,626,306 A (MILLER III et al) 06 May 1997, see whole document.	1-7

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
C document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

 Date of the actual completion of the international search
12 MAY 1998

 Date of mailing of the international search report
19 JUN 1998

 Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

 Authorized officer *John M. Jillions*
JOHN M. JILLIONS
Telephone No. 703-308-2685